

RS-COMPACT range

The RENNER COMPACT UNITS
Ideal for continuous operation!

Output: 3.0 and 4.0 kW
operating pressures 7.,5 / 10 / 13 bar (g)

Technical Data

Type	free air delivered at						Motor power		Receivers litre	Dimensions width x depth x height mm	Weight approx. kg
	7.5 bar /110psi (g)		10 bar /145psi (g)		13 bar /190psi (g)		kW	HP			
	cfm	m ³ /min	cfm	m ³ /min	cfm	m ³ /min					
RS-COMPACT 3,0	14	0,39	11	0,30	8	0,22	3,0	4,0	-	445 x 1000 x 445 mm	120
RS-COMPACT 4,0	19	0,54	16	0,44	12	0,33	4,0	5,5	-	445 x 1000 x 445 mm	125
RSD-COMPACT 3,0	14	0,39	11	0,30	8	0,22	3,0	4,0	90	445 x 1000 x 895 mm	145
RSD-COMPACT 3,0	14	0,39	11	0,30	8	0,22	3,0	4,0	250	680 x 1450 x 1005 mm	220
RSD-COMPACT 4,0	19	0,54	16	0,44	12	0,33	4,0	5,5	90	445 x 1000 x 895 mm	150
RSD-COMPACT 4,0	19	0,54	16	0,44	12	0,33	4,0	5,5	250	680 x 1450 x 1005 mm	225
RSDK-COMPACT 3,0	14	0,39	11	0,30	8	0,22	3,0	4,0	250	680 x 1450 x 1005 mm	240
RSDK-COMPACT 4,0	19	0,54	16	0,44	12	0,33	4,0	5,5	250	680 x 1450 x 1005 mm	245