

RSD range

screw compressors
on horizontal pressure vessels
from 3 to 15 kW

Technical data :

| Type | free air delivered f.a.d. m ³ /min at: | | | | motor power | | dimensions width x depth x height | weight kg |
|----------|---|--------|--------|--------|-------------|------|--------------------------------------|--------------|
| | 7,5 bar | 10 bar | 13 bar | 15 bar | kW | HP | | |
| RSD 3,0 | 0,41 | 0,32 | 0,24 | 0,21 | 3,0 | 4,0 | 700 x 1650 x 1450 mm | 260 |
| RSD 4,0 | 0,56 | 0,46 | 0,35 | 0,30 | 4,0 | 5,5 | 700 x 1650 x 1450 mm | 260 |
| RSD 5,5 | 0,77 | 0,65 | 0,53 | 0,45 | 5,5 | 7,5 | 700 x 1650 x 1450 mm | 270 |
| RSD 7,5 | 1,10 | 0,95 | 0,74 | 0,63 | 7,5 | 10,0 | 700 x 1650 x 1450 mm | 280 |
| RSD 9,0 | – | 1,09 | 0,86 | 0,76 | 9,0 | 12,0 | 700 x 1650 x 1450 mm | 290 |
| RSD 11,0 | 1,76 | 1,50 | 1,16 | 0,93 | 11,0 | 15,0 | 800 x 1990 x 1750 mm | 440 |
| RSD 15,0 | 2,24 | 1,96 | 1,51 | 1,24 | 15,0 | 20,0 | 800 x 1990 x 1750 mm | 460 |