

RENNER screw compressor with refrigeration dryer and frequency control

Type RSK 3,0 – 45,0

Technical data:															
Type		f. a. d.								Motor power kW HP		Dimension mm width x depth x height			Weight approx. kg
		7,5 bar		10 bar		13 bar		15 bar							
		cfm	m ³ /min	cfm	m ³ /min	cfm	m ³ /min	cfm	m ³ /min						
RSK	3,0	15	0,41	12	0,32	9	0,24	8	0,21	3,0	4,0	567 x 1115 x 900			190
RSK	4,0	20	0,56	17	0,46	13	0,35	11	0,30	4,0	5,5	567 x 1115 x 900			190
RSK	5,5	28	0,77	23	0,65	19	0,53	16	0,45	5,5	7,5	567 x 1115 x 900			210
RSK	7,5	39	1,10	34	0,95	26	0,74	23	0,63	7,5	10,0	567 x 1115 x 900			220
RSK	9,0	–	–	39	1,09	31	0,86	27	0,76	9,0	12,0	567 x 1115 x 900			235
RSK	11,0	63	1,76	53	1,50	41	1,16	33	0,93	11,0	15,0	664 x 1522 x 1117			470
RSK	15,0	79	2,24	70	1,96	54	1,51	44	1,24	15,0	20,0	664 x 1522 x 1117			490
RSK	18,5	103	2,91	93	2,62	78	2,20	67	1,89	18,5	25,0	791 x 1873 x 1290			630
RSK	22,0	123	3,46	110	3,10	94	2,66	82	2,31	22,0	30,0	791 x 1873 x 1290			710
RSK1-	30,0	155	4,38	142	4,01	125	3,52	107	3,02	30,0	40,0	791 x 1873 x 1290			730
RSK2-	30,0	179	5,05	152	4,28	133	3,76	120	3,40	30,0	40,0	933 x 2030 x 1574			890
RSK	37,0	218	6,15	185	5,24	161	4,56	147	4,15	37,0	50,0	933 x 2030 x 1574			940
RSK	45,0	257	7,25	230	6,51	196	5,55	178	5,03	45,0	60,0	933 x 2030 x 1574			980