

# RENNER screw compressor with refrigeration dryer and frequency control

## Type RSKF 4,0 – 45,0

Technical data									
Type	free air delivered f.a.d. m <sup>3</sup> /min at:				motor power		dimensions width x depth x height mm	weight kg	
	7,5 bar	10 bar	13 bar	15 bar	kW	HP			
RSKF 4,0	0,17 - 0,56	0,14 - 0,46	0,10 - 0,34	0,09 - 0,30	4,0	5,5	567 x 1115 x 900	220	
RSKF 5,5	0,23 - 0,77	0,20 - 0,65	0,16 - 0,53	0,14 - 0,45	5,5	7,5	567 x 1115 x 900	230	
RSKF 7,5	0,33 - 1,10	0,29 - 0,95	0,22 - 0,74	0,19 - 0,63	7,5	10,0	567 x 1115 x 900	245	
RSKF 9,0	–	0,33 - 1,09	0,26 - 0,86	0,23 - 0,76	9,0	12,0	567 x 1115 x 900	275	
RSKF 11,0	0,52 - 1,76	0,45 - 1,50	0,35 - 1,16	0,28 - 0,93	11,0	15,0	664 x 1522 x 1117	490	
RSKF 15,0	0,67 - 2,24	0,59 - 1,96	0,45 - 1,51	0,37 - 1,24	15,0	20,0	664 x 1522 x 1117	500	
RSKF 18,5	0,87 - 2,91	0,79 - 2,62	0,66 - 2,20	0,57 - 1,89	18,5	25,0	791 x 1873 x 1290	680	
RSKF 22,0	1,04 - 3,46	0,93 - 3,10	0,80 - 2,66	0,69 - 2,31	22,0	30,0	791 x 1873 x 1290	710	
RSKF1-30,0	1,31 - 4,38	1,20 - 4,01	1,06 - 3,52	0,91 - 3,02	30,0	40,0	791 x 1873 x 1290	755	
RSKF2-30,0	1,52 - 5,05	1,28 - 4,28	1,13 - 3,76	1,02 - 3,40	30,0	40,0	933 x 2030 x 1574	940	
RSKF 37,0	1,85 - 6,15	1,57 - 5,24	1,37 - 4,56	1,25 - 4,15	37,0	50,0	933 x 2030 x 1574	990	
RSKF 45,0	2,18 - 7,25	1,95 - 6,51	1,67 - 5,55	1,51 - 5,03	45,0	60,0	933 x 2030 x 1574	1050	